












## Axis modular cameras

	AXIS P12 Series										
	AXIS P1290-E	AXIS P1280-E	AXIS P1275	AXIS P1265	AXIS P1264	AXIS P1254	AXIS P1245	AXIS P1244	AXIS P1224-E	AXIS P1214	AXIS P1214-E
											
Max. video resolution	208x156	208x156	1920x1080 (2.1 MP)	1920x1080 (2.1 MP)	1280x720 (1 MP)	1280x720 (1 MP)	1920x1080 (2.1 MP)	1280x720 (1 MP)	1280x720 (1 MP)	1280x720 (1 MP)	1280x720 (1 MP)
Sensor size/Lens/ Horizontal field of view	Uncooled microbolometer Athermalized lens 4 mm, F1.2, 35.4°	Uncooled microbolometer Athermalized lens 4 mm, F1.2, 35.4°	1/2.9", 2.8 – 6 mm, F2.0, 99° – 53°	1/2.9", 3.7 mm, F2.5, 91°	1/4", 3.7 mm, F2.5, 57°	1/4", 2.1 mm, F2.2, 102°	1/2.9", 2.8 mm, F2.0, 111°	1/4", 2.1 mm, F2.2, 102°	1/4", 1.56 mm, F2.8, 145°	1/4", 3.7 mm, F2.5, 57°	1/4", 2.8 mm, F2.0, 81°
Day and night	-	-	-	-	-	-	-	-	-	-	-
Min. illumination (lux) Color/B&W	-	-	0.22/-	0.27/-	0.5/-	0.4/-	0.22/-	0.4/-	1.8/-	1.2/-	1.0/-
Max. frames per second	8.3 <sup>1</sup>	8.3 <sup>1</sup>	25/30	25/30	25/30	25/30	25/30	25/30	25/30	25/30	25/30
Sensitivity	NETD < 100 mK	NETD < 100 mK	-	-	-	-	-	-	-	-	-
Detection range (m/yd.)	166/182 <sup>2</sup> 511/559 <sup>3</sup>	166/182 <sup>2</sup> 511/559 <sup>3</sup>	-	-	-	-	-	-	-	-	-
Audio support/ Built-in mic	- / -	- / -	- / -	- / -	- / -	- / -	- / -	- / -	- / -	- / -	- / -
Product specific analytics (for standard analytics, see page 43)	Video Motion Detection	Video Motion Detection	Standard analytics	Standard analytics	Standard analytics	Standard analytics	Standard analytics	Standard analytics	Standard analytics	Standard analytics	Standard analytics
Power	PoE Class 2	PoE Class 2	PoE Class 2	PoE Class 2	PoE Class 2	PoE Class 2	PoE Class 2	PoE Class 2	PoE Class 2, DC	PoE Class 2, DC	PoE Class 2, DC
In-/output ports	-	-	-	-	-	-	-	-	1/1	1/1	1/1
Operating temperature	Main unit: -20 °C to 50 °C (-4 °F to 122 °F) Thermal sensor unit: -30 °C to 55 °C (-22 °F to 131 °F)	Main unit: -20 °C to 50 °C (-4 °F to 122 °F) Thermal sensor unit: -30 °C to 55 °C (-22 °F to 131 °F)	-20 °C to 50 °C (-4 °F to 122 °F)	-20 °C to 50 °C (-4 °F to 122 °F)	-20 °C to 50 °C (-4 °F to 122 °F)	-20 °C to 50 °C (-4 °F to 122 °F)	-20 °C to 50 °C (-4 °F to 122 °F)	-20 °C to 50 °C (-4 °F to 122 °F)	-20 °C to 50 °C (-4 °F to 122 °F)	-20 °C to 50 °C (-4 °F to 122 °F)	-20 °C to 50 °C (-4 °F to 122 °F)
Outdoor ready approvals	IP66/IP67/NEMA 4X	IP66/IP67/NEMA 4X	-	-	-	-	-	-	IP66/NEMA 4X	-	IP66/NEMA 4X
WDR	-	-	Forensic Capture	Forensic Capture	WDR	WDR	Forensic Capture	WDR	-	-	-
Lightfinder	-	-	-	-	-	-	-	-	-	-	-
Zipstream/H.264/H.265	✓ / ✓ / -	✓ / ✓ / -	✓ / ✓ / -	✓ / ✓ / -	✓ / ✓ / -	✓ / ✓ / -	✓ / ✓ / -	✓ / ✓ / -	- / ✓ / -	- / ✓ / -	- / ✓ / -
OptimizedIR/Built-in IR	- / -	- / -	- / -	- / -	- / -	- / -	- / -	- / -	- / -	- / -	- / -
Special features	Palette setting	Palette setting	Varifocal lens	Pinhole lens	Pinhole lens	Standard lens	Standard lens	Standard lens	Standard lens	Pinhole lens	Pinhole lens

1. Up to 30 fps within EU, Norway, Switzerland, Canada, USA, Japan, Australia, New Zealand. Up to 8.3 fps in other countries. Frame rate above 9 fps may be subject to export control regulations

2. Detection range measured for humans, 1.8 x 0.5 m, calculated with Johnson's criteria

3. Detection range measured for vehicles, 4 x 1.5 m, calculated with Johnson's criteria